



- A EXISTING PAVEMENT (VARIES)
- 1 0" MIN. HOT MIXED, HOT LAID ASPHALT CONCRETE, ITEM 404
- 2 1 1/4" HOT MIXED, HOT LAID ASPHALT CONCRETE, ITEM 404
- 3 1 1/4" HOT MIXED, HOT LAID ASPHALT CONCRETE, ITEM 402
- 4 TACK COAT, BITUMINOUS MATERIAL, 702.02 RC-70 OR RC-250 OR 702.04 RS-1, RS-2 OR MS-2 APPLIED AT A RATE OF 0.1 GAL. PER SQ. YD. AND COVER CONSISTING OF CRUSHED GRAVEL OR LIMESTONE, SIZE NO. 9, ITEM 407.
- 5 8" PORTLAND CEMENT CONCRETE WITH INTEGRAL CURB, ITEM 453

ITEM NUMBERS SHOWN REFER TO THE CURRENT STATE OF OHIO, DEPARTMENT OF TRANSPORTATION "CONSTRUCTION AND MATERIAL SPECIFICATIONS" AND THE CURRENT CITY OF COLUMBUS "CONSTRUCTION AND MATERIAL SPECIFICATIONS".

APPROVED
EVANS, MECHWART, HAMBLETON & TILTON, INC.

By

Charles W. Board Jr.
CITY ADMINISTRATOR

SPECIAL 8"
WIDENING SECTION
WITH
INTEGRAL CURB

CITY OF
GROVE CITY, OHIO

STANDARD
CONSTRUCTION DRAWING

REV.

DATE
12-10-87

DWG. NO
C-GC-55